NSN 5905-00-543-8525

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-543-8525 **Section Quantity:** 2 **Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** 1.8750 inches Pilot Length: 0.0620 inches **Overall Length:** 2.258 inches **Undercut Diameter:** 1.875 inches **Undercut Width:** 0.0620 inches **Body Diameter:** 2.000 inches **Angle Of Mounting Hole In Deg:** 90.0 **Angle Between Centerlines Of Mounting Holes In Deg:** 120.0 **Shaft Diameter:** 0.2497 inches **Shaft Length:** 0.645 inches **Body Length:** 1.613 inches **Overall Diameter:** 2.281 inches **Mounting Lip Diameter:** 2.0000 inches **Mounting Lip Depth:** 0.0620 inches **Mounting Hole/stud Circle Diameter:** 1.250 inches **Shaft Style:** Round **Shaft Bearing Type:** Ball

Actuator Type: Single shaft

NSN 5905-00-543-8525

Precision Wire Wound Variable Resistor - Page 2 of 3



Effective Electrical Rotation In Deg Angular Rotation: 358.0 **Maximum Starting Torque:** 0.80 inch-ounces **Maximum Running Torque:** 0.60 inch-ounces **Shaft End Play:** 0.00500 inches **Shaft Runout:** 0.001 inches **Lateral Runout:** 0.006 inches **Pilot Diameter Runout:** 0.00150 inches **Shaft Radial Play:** 0.002 inches **Fragility Factor:** Moderately rugged **Terminal Location:** Radially positioned over less than half the circumference **Mounting Method:** Clamp ring **Features Provided:** Humidity proof **Cubic Measure:** 6.452 cubic inches **Electrical Resistance Per Section:** 50.000 kilohms 1st section **Rotary Actuator Travel In Angular Deg:** 360.0 **Function Conformity Tolerance Per Section:** -0.50 to 0.50 all sections Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 80.0 all sections Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -20.0 to 20.0 all sections **Power Dissipation Rating Per Section In Watts:** 4.0 free air all sections **Function Conformity Per Section:** All sections independent linearity **Resistance Tolerance Per Section In Percent:**

Continuous motion

-5.0 to 5.0 all sections

Actuator Travel Control Feature:

NSN 5905-00-543-8525

Function Characteristic Per Section:

Precision Wire Wound Variable Resistor - Page 3 of 3



All sections linear
Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per De
-20.0 to 20.0 all sections
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 all sections
Unpackaged Unit Weight:

Per Deg Celsius:

Terminal Type And Quantity:

6 turret

5.00 ounces

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0