NSN 5905-00-543-8808

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-543-8808 **Section Quantity: Body Style:** Cylindrical bushing mounted **Overall Length:** 1.312 inches **Body Diameter:** Between 1.609 inches and 1.641 inches **Mounting Bushing Length:** 0.375 inches **Body Length:** Between 0.547 inches and 0.578 inches **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 275.0 **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Radially positioned over less than half the circumference **Mounting Method:** Standard bushing **Electrical Resistance Per Section:** 10.000 kilohms single section **Rotary Actuator Travel In Angular Deg:** 294.0 **Power Dissipation Rating Per Section In Watts:** 4.0 free air single section **Resistance Tolerance Per Section In Percent:** -10.0 to 10.0 single section **Actuator Travel Control Feature:** Stops Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 40.0 single section **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:**

3 tab, solder lug

NSN 5905-00-543-8808

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A002a0