NSN 5905-00-543-8818

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-543-8818 **Section Quantity: Body Style:** Rectangular w/mounting holes/slots **Reliability Indicator:** Not established **Overall Length:** 1.472 inches **Terminal Length:** 0.160 inches **Overall Width:** 0.284 inches **Mounting Hole Diameter:** Between 0.088 inches and 0.098 inches **Shaft Diameter:** 0.125 inches **Shaft Length:** Between 0.057 inches and 0.067 inches **Body Length:** Between 1.245 inches and 1.255 inches **Body Width:** 0.284 inches **Body Height:** 0.328 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Lateral Distance Between Mounting Hole Centers:** Between 0.995 inches and 1.005 inches **Mounting Facility Quantity: Terminal Location:** Rear end **Mounting Method:** Unthreaded hole **Electrical Resistance Per Section:** 10.000 kilohms single section Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

140.0 single section

Power Dissipation Rating Per Section In Watts:

0.4 free air single section

NSN 5905-00-543-8818

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Resistance Tolerance Per Section In Percent:

-5.0 to 5.0 single section

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

2 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0