NSN 5905-00-546-3055

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-546-3055 **Section Quantity:** 1 **Body Style:** Rectangular w/mounting holes/slots **Reliability Indicator:** Not established **Overall Length:** 1.308 inches **Terminal Length:** 6.000 inches **Overall Height:** 0.315 inches **Overall Width:** 0.190 inches **Mounting Hole Diameter:** 0.093 inches **Shaft Diameter:** 0.115 inches **Shaft Length:** 0.058 inches **Body Length:** 1.250 inches **Body Width:** 0.190 inches **Body Height:** 0.315 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Lateral Distance Between Mounting Hole Centers:** 1.000 inches **Mounting Facility Quantity:** 2 **Terminal Location:** Rear end **Mounting Method:** Unthreaded hole **Electrical Resistance Per Section:** 25.000 kilohms single section Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

150.0 single section

NSN 5905-00-546-3055

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-100.0 to 100.0 single section

Power Dissipation Rating Per Section In Watts:

1.0 free air single section

Resistance Tolerance Per Section In Percent:

-10.0 to 10.0 single section

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 wire lead

Shelf Life:

_

N/a

Unit Of Measure:

__

Demilitarization:

No

Fiig:

A002a0