

View Online at <https://aerobasegroup.com/nsn/5905-00-549-1599>

**Section Quantity:**

1

**Body Style:**

Cylindrical studs mounted

**Reliability Indicator:**

Not established

**Body Diameter:**

3.000 inches

**Shaft Diameter:**

0.250 inches

**Shaft Length:**

0.750 inches

**Body Length:**

0.625 inches

**Mounting Hole/stud Circle Diameter:**

1.750 inches

**Shaft Style:**

Round

**Shaft Bearing Type:**

Ball

**Actuator Type:**

Single shaft

**Effective Electrical Rotation In Deg Angular Rotation:**

356.0

**Maximum Starting Torque:**

1.00 inch-ounces

**Maximum Running Torque:**

1.00 inch-ounces

**Shaft End Play:**

0.00500 inches

**Shaft Runout:**

0.002 inches

**Lateral Runout:**

0.002 inches

**Pilot Diameter Runout:**

0.00100 inches

**Shaft Radial Play:**

0.002 inches

**Screw Thread Diameter:**

0.164 inches

**Screw Thread Series Designator:**

Unc

**Screw Thready Qty Per Inch (tpi):**

32.0

**Mounting Facility Quantity:**

3

**Terminal Location:**

Radially positioned over less than half the circumference

**Mounting Method:**

Threaded hole

**Features Provided:**

Nonmetallic shaft

**Electrical Resistance Per Section:**

35.000 kilohms single section

**Rotary Actuator Travel In Angular Deg:**

360.0

**Function Conformity Tolerance Per Section:**

-0.10/+0.10 single section

**Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:**

125.0 single section

**Power Dissipation Rating Per Section In Watts:**

6.0 free air single section

**Function Conformity Per Section:**

Single section independent linearity

**Resistance Tolerance Per Section In Percent:**

-10.0/+10.0 single section

**Actuator Travel Control Feature:**

Continuous motion

**Function Characteristic Per Section:**

Single section linear

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

40.0 single section

**Terminal Type And Quantity:**

3 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A002a0