NSN 5905-00-549-1773

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-549-1773 **Section Quantity: Reliability Indicator:** Not established First Flat Length: 0.469 inches Flat Height: 0.218 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.875 inches **Shaft Style:** Round, flatted **Actuator Type:** Single shaft **Nonturn Device Location:** At 9 oclock **Nonturn Device Radius:** 0.531 inches **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Mounting Method:** Standard bushing **Electrical Resistance Per Section:** 150.000 kilohms single section **Power Dissipation Rating Per Section In Watts:** 0.5 free air single section **Resistance Tolerance Per Section In Percent:** -20.0/+20.0 single section **Terminal Type And Quantity:** 3 tab, solder lug **Unit Of Measure:**

Shelf Life:
N/a
Unit Of Measure:
-Demilitarization:
No

NSN 5905-00-549-1773

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Fiig:

A002a0