## NSN 5905-00-549-2560

Film Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-549-2560

Tempurature Coefficient Of Resistance in Ppm Per Deg Celsius:  10.700 kilohms  Resistance Tolerance in Percent:  1.0004-1.000  Ambient Tempurature in Deg Celsius At Full Rated Power:  125.0  Ambient Tempurature in Deg Celsius At Zero Percent Rated Power:  125.0  Ambient Tempurature in Deg Celsius At Zero Percent Rated Power:  125.0  Tempurature Range Of Tempurature Coefficient in Deg Celsius:  55.0/+175.0  Tempurature Range Of Tempurature Coefficient in Deg Celsius:  55.0/+175.0  Tempurature Method:
Electrical Resistance:  10.700 kilohms  Resistance Tolerance in Percent:  1.000/+1.000  Ambient Tempurature in Deg Celsius At Full Rated Power:  125.0  Ambient Tempurature in Deg Celsius At Zero Percent Rated Power:  125.0  Immurature Range Of Tempurature Coefficient in Deg Celsius:  55.0/+175.0  Immurature Range Of Tempurature Coefficient in Deg Celsius:  55.0/+175.0  Immurature Range Of Tempurature Coefficient in Deg Celsius:  55.0/+175.0  Immurature Range Of Tempurature Coefficient in Deg Celsius:  55.0/+175.0  Immurature Range Of Tempurature Coefficient in Deg Celsius:  55.0/+175.0  Immurature Range Of Tempurature Coefficient in Deg Celsius:  55.0/+175.0  Immurature Range Of Tempurature Coefficient in Deg Celsius:  55.0/+175.0  Immurature Range Of Tempurature Coefficient in Deg Celsius:  55.0/+175.0  Immurature Range Of Tempurature Coefficient in Deg Celsius:  55.0/+175.0  Immurature Range Of Tempurature Coefficient in Deg Celsius:  55.0/+175.0  Immurature Range Of Tempurature Range Of Tempurature Coefficient in Deg Celsius:  55.0/+175.0  Immurature Range Of Tempurature Range Of Tempurature Coefficient in Deg Celsius:  50.00  Immurature Range Of Tempurature Range Of Selsius At Zero Percent Rated Power:  10.00
Resistance Tolerance In Percent:  1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power:  125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius:  55.0/+175.0 Inclosure Method: Encapsulated Terminal Type:  Wire lead Reliability Indicator:  Established Reliability Failure Rate Level In Percent:  1.000 Body Diameter:  Between 0.219 inches and 0.328 inches Body Length:  Between 0.88 inches and 0.875 inches  Power Dissipation Rating In Watts:  1.500 free air  Style Designator:  Axial terminal each end Test Data Document:  81349-milr55182/6 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
Resistance Tolerance In Percent:  1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power:  125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius:  55.0+175.0 Inclosure Method: Encapsulated Terminal Type:  Wire lead Reliability Indicator:  Established Reliability Failure Rate Level In Percent:  1.000 Body Diameter:  Between 0.219 inches and 0.328 inches Body Length:  Between 0.88 inches and 0.875 inches Power Dissipation Rating In Watts:  0.500 free air  Style Designator:  Axial terminal each end Test Data Document:  81349-milr55182/6 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 Tempurature Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 1.000 Body Diameter: Between 0.219 inches and 0.328 inches Body Length: Between 0.888 inches and 0.875 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr55182/6 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
Ambient Tempurature In Deg Celsius At Full Rated Power:  125.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  175.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  55.0/+175.0  Inclosure Method:  Encapsulated  Terminal Type:  Wire lead  Reliability Indicator:  Established  Reliability Failure Rate Level In Percent:  1.000  Body Diameter:  36thween 0.219 inches and 0.328 inches  Body Length:  28thween 0.888 inches and 0.875 inches  Power Dissipation Rating In Watts:  0.500 free air  Style Designator:  Axial terminal each end  Test Data Document:  81349-milr55182/6 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification ormat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  175.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  55.0/+175.0  Inclosure Method:  Encapsulated  Terminal Type:  Wire lead  Reliability Indicator:  Established  Reliability Failure Rate Level In Percent:  1.000  Body Diameter:  Between 0.219 inches and 0.328 inches  Body Length:  Between 0.888 inches and 0.875 inches  Power Dissipation Rating In Watts:  0.500 free air  Style Designator:  Avial terminal each end  Test Data Document:  81349-mili55182/6 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  175.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  55.0/+175.0  Inclosure Method:  Encapsulated  Terminal Type:  Wire lead  Reliability Indicator:  Established  Reliability Failure Rate Level In Percent:  1.000  Body Diameter:  Between 0.219 inches and 0.328 inches  Body Length:  Between 0.688 inches and 0.875 inches  Power Dissipation Rating In Watts:  0.500 free air  Style Designator:  Axial terminal each end  Test Data Document:  81349-millr55182/6 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
Tempurature Range Of Tempurature Coefficient In Deg Celsius:  55.0/+175.0  Inclosure Method: Encapsulated  Terminal Type:  Wire lead  Reliability Indicator: Established  Reliability Failure Rate Level In Percent:  1.000  Body Diameter: Between 0.219 inches and 0.328 inches  Body Length: Between 0.688 inches and 0.875 inches  Power Dissipation Rating In Watts:  0.500 free air  Style Designator:  Axial terminal each end  Test Data Document:  81349-millr55182/6 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
Tempurature Range Of Tempurature Coefficient In Deg Celsius:  55.0/+175.0  inclosure Method:  Encapsulated  Terminal Type:  Wire lead  Reliability Indicator:  Established  Reliability Failure Rate Level In Percent:  1.000  Body Diameter:  Between 0.219 inches and 0.328 inches  Body Length:  Between 0.688 inches and 0.875 inches  Power Dissipation Rating In Watts:  0.500 free air  Style Designator:  Axial terminal each end  Test Data Document:  81349-milr55182/6 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
inclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 1,000 Body Diameter: Between 0.219 inches and 0.328 inches Body Length: Between 0.688 inches and 0.875 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator: Axial terminal each end Fest Data Document: 81349-milr55182/6 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
Inclosure Method: Encapsulated  Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 1,000 Body Diameter: Between 0.219 inches and 0.328 inches Body Length: Between 0.688 inches and 0.875 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator: Avial terminal each end  Test Data Document: 81349-milr55182/6 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
Encapsulated  Ferminal Type:  Wire lead  Reliability Indicator:  Established  Reliability Failure Rate Level In Percent:  1.000  Body Diameter:  Between 0.219 inches and 0.328 inches  Body Length:  Between 0.688 inches and 0.875 inches  Power Dissipation Rating In Watts:  1.500 free air  Style Designator:  Avial terminal each end  Fest Data Document:  31349-milr55182/6 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
Terminal Type:  Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 1.000 Body Diameter: Between 0.219 inches and 0.328 inches Body Length: Between 0.688 inches and 0.875 inches Power Dissipation Rating In Watts: 0.500 free air  Style Designator: Axial terminal each end Test Data Document: 81349-milr55182/6 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 1,000 Body Diameter: Between 0,219 inches and 0,328 inches Body Length: Between 0,688 inches and 0,875 inches Power Dissipation Rating In Watts: 0,500 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr55182/6 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
Reliability Indicator: Established Reliability Failure Rate Level In Percent: 1.000 Body Diameter: Between 0.219 inches and 0.328 inches Body Length: Between 0.688 inches and 0.875 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator: Axial terminal each end Test Data Document: B1349-milr55182/6 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
Established  Reliability Failure Rate Level In Percent:  1.000  Body Diameter:  Between 0.219 inches and 0.328 inches  Body Length:  Between 0.688 inches and 0.875 inches  Power Dissipation Rating In Watts:  0.500 free air  Style Designator:  Axial terminal each end  Test Data Document:  81349-milr55182/6 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
Reliability Failure Rate Level In Percent:  1.000  Body Diameter:  Between 0.219 inches and 0.328 inches  Body Length:  Between 0.688 inches and 0.875 inches  Power Dissipation Rating In Watts:  0.500 free air  Style Designator:  Axial terminal each end  Test Data Document:  81349-milr55182/6 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
Body Diameter: Between 0.219 inches and 0.328 inches Body Length: Between 0.688 inches and 0.875 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator: Axial terminal each end Test Data Document: 01349-milr55182/6 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
Body Diameter: Between 0.219 inches and 0.328 inches Body Length: Between 0.688 inches and 0.875 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator: Axial terminal each end Test Data Document: B1349-milr55182/6 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
Between 0.219 inches and 0.328 inches  Body Length: Between 0.688 inches and 0.875 inches  Power Dissipation Rating In Watts:  0.500 free air  Style Designator:  Axial terminal each end  Test Data Document:  81349-milr55182/6 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
Body Length: Between 0.688 inches and 0.875 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr55182/6 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
Between 0.688 inches and 0.875 inches  Power Dissipation Rating In Watts:  0.500 free air  Style Designator:  Axial terminal each end  Test Data Document:  31349-milr55182/6 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
Power Dissipation Rating In Watts:  0.500 free air  Style Designator:  Axial terminal each end  Test Data Document:  31349-milr55182/6 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
5.500 free air Style Designator: Axial terminal each end Fest Data Document: B1349-milr55182/6 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
Style Designator:  Axial terminal each end  Test Data Document:  B1349-milr55182/6 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
Axial terminal each end  Test Data Document:  B1349-milr55182/6 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
<b>Test Data Document:</b> 31349-milr55182/6 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
81349-milr55182/6 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A001a0