NSN 5905-00-549-3458

Section Quantity:

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-549-3458

Reliability Indicator:
Not established
Shaft Diameter:
0.125 inches
Shaft Length:
0.750 inches
Mounting Bushing Length:
0.375 inches
Body Length:
0.750 inches
Body Width:
0.438 inches
Body Height:
0.938 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Nonturn Device Location:
At 9 oclock
Nonturn Device Radius:
0.234 inches
Screw Thread Diameter:
0.250 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
500.000 ohms single section
Power Dissipation Rating Per Section In Watts:
1.5 free air single section
Function Conformity Per Section:
Single section independent linearity
Resistance Tolerance Per Section In Percent:
-5.0 to 5.0 single section
Standard Taper Curve Per Section:
A single section

NSN 5905-00-549-3458

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Special Features:
Equipped w/shaft le

locking device

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0