## NSN 5905-00-549-3927

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-549-3927

Section Quantity:
1
Shaft Diameter:
0.250 inches
Shaft Length:
0.625 inches
Mounting Bushing Length:
0.500 inches
Body Length:
1.266 inches
Body Width:
0.625 inches
Body Height:
1.375 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Nonturn Device Location:
At 9 oclock
Nonturn Device Radius:
0.531 inches
Screw Thread Diameter:
0.375 inches
0.373 mones
Screw Thread Series Designator:
Screw Thread Series Designator:
Screw Thread Series Designator: Unef
Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi):
Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): 32.0
Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): 32.0 Mounting Method:
Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): 32.0 Mounting Method: Standard bushing
Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): 32.0 Mounting Method: Standard bushing Electrical Resistance Per Section:
Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): 32.0 Mounting Method: Standard bushing Electrical Resistance Per Section: 25.000 ohms single section
Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): 32.0 Mounting Method: Standard bushing Electrical Resistance Per Section: 25.000 ohms single section Power Dissipation Rating Per Section In Watts:
Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): 32.0 Mounting Method: Standard bushing Electrical Resistance Per Section: 25.000 ohms single section Power Dissipation Rating Per Section In Watts: 2.0 free air single section
Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): 32.0 Mounting Method: Standard bushing Electrical Resistance Per Section: 25.000 ohms single section Power Dissipation Rating Per Section In Watts: 2.0 free air single section Function Conformity Per Section:
Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): 32.0 Mounting Method: Standard bushing Electrical Resistance Per Section: 25.000 ohms single section Power Dissipation Rating Per Section In Watts: 2.0 free air single section Function Conformity Per Section: Single section independent linearity
Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): 32.0 Mounting Method: Standard bushing Electrical Resistance Per Section: 25.000 ohms single section Power Dissipation Rating Per Section In Watts: 2.0 free air single section Function Conformity Per Section: Single section independent linearity Resistance Tolerance Per Section In Percent:

Special Features:

Equipped w/shaft locking device

## NSN 5905-00-549-3927

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A002a0