NSN 5905-00-549-3930

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-549-3930 **Section Quantity: Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** 1.531 inches **Terminal Length:** 0.422 inches **Body Diameter:** 1.656 inches **Shaft Diameter:** Between 0.248 inches and 0.250 inches **Shaft Length:** 0.750 inches **Mounting Bushing Length:** 0.375 inches **Body Length:** 0.781 inches **Overall Diameter:** 2.078 inches **Shaft Style:** Round **Contact Arm Electrical Off Position:** Fully ccw **Actuator Type:** Single shaft **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Radially positioned over less than half the circumference **Mounting Method:** Standard bushing **Electrical Resistance Per Section:**

500.000 ohms single section

Power Dissipation Rating Per Section In Watts:

2.0 free air single section

NSN 5905-00-549-3930

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



5	esistance	Tolerance	Per Section	In Percent:
۲	esistance	i olei ance	rei Section	ın Fercent.

-10.0 to 10.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0