NSN 5905-00-549-4402



Nonprecision Wire Wound Variable Resistor - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5905-00-549-4402 **Section Quantity: Shaft Diameter:** 0.250 inches **Shaft Length:** 0.875 inches **Shaft Style:** Round Switch Type: Rotary **Switch Voltage Rating In Volts:** 125.0 **Actuator Type:** Single shaft **Nonturn Device Location:** At 9 oclock **Nonturn Device Radius:** 0.531 inches **Switch Operating Position:** Start of rotation **Switch Contact Arrangement:** Single pole, single throw, normally open, both positions maintained **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Mounting Method:** Standard bushing **Features Provided:**

Switch **Electrical Resistance Per Section:** 1.000 kilohms single section **Power Dissipation Rating Per Section In Watts:** 2.0 free air single section **Resistance Tolerance Per Section In Percent:** -10.0 to 10.0 single section **Switch Current Type And Rating In Amps:**

3.000 ac/dc

Standard Taper Curve Per Section:

A single section

NSN 5905-00-549-4402

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Terminal Type And Quantity	/ :
----------------------------	------------

5 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0