NSN 5905-00-549-6129

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-549-6129 **Section Quantity:** 2 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** 2.734 inches **Body Diameter:** 1.531 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 1.312 inches **Mounting Bushing Length:** 0.375 inches **Body Length:** 1.406 inches **Shaft Style:** Round **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 295.0 **Nonturn Device Location:** At 9 oclock **Nonturn Device Radius:** 0.531 inches **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Radially positioned over less than half the circumference **Mounting Method:** Standard bushing **Electrical Resistance Per Section:**

100.000 ohms all sections

Rotary Actuator Travel In Angular Deg:

295.0

NSN 5905-00-549-6129

Fiig: A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 60.0 all sections **Power Dissipation Rating Per Section In Watts:** 4.0 free air all sections **Resistance Tolerance Per Section In Percent:** -10.0 to 10.0 all sections **Actuator Travel Control Feature:** Stops Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 25.0 all sections **Standard Taper Curve Per Section:** A all sections **Terminal Type And Quantity:** 6 tab, solder lug Shelf Life: N/a **Unit Of Measure: Demilitarization:** No