NSN 5905-00-549-6354

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-549-6354

·					
Section Quantity:					
1					
Body Style:					
Cylindrical bushing mounted					
Reliability Indicator:					
Not established					
Body Diameter:					
2.406 inches					
Shaft Diameter:					
0.250 inches					
Shaft Length:					
0.688 inches					
Mounting Bushing Length:					
0.375 inches					
Body Length:					
1.531 inches					
Shaft Style:					
Round, slotted					
Actuator Type:					
Single shaft					
Nonturn Device Location:					
At 3 oclock and at 6 oclock and at 9 oclock and at 12 oclock					
Nonturn Device Radius:					
0.500 inches					
Screw Thread Diameter:					
0.375 inches					
Screw Thread Series Designator:					
Unef					
Screw Thready Qty Per Inch (tpi):					
32.0					
Terminal Location:					
Radially positioned over less than half the circumference					
Mounting Method:					
Standard bushing					
Electrical Resistance Per Section:					
8.000 ohms single section					
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:					
340.0 single section					
Power Dissipation Rating Per Section In Watts:					
50.0 free air single section					
Resistance Tolerance Per Section In Percent:					

-10.0 to 10.0 single section

NSN 5905-00-549-6354

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Ambient Tempurature	In Deg Celsius F	Per Section	At Full Rated	Power
40.0 single section				

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0