## NSN 5905-00-549-7453

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-549-7453

	Quantity:
1	
Body Sty	
	al bushing mounted
	y Indicator:
Not estab	
Overall L	Length:
1.187 inc	hes
Body Dia	ameter:
1.062 inc	hes
Shaft Dia	ameter:
0.250 inc	hes
Shaft Le	ngth:
0.625 inc	hes
Mountin	g Bushing Length:
0.375 inc	hes
Body Le	ngth:
0.562 inc	hes
Shaft Sty	/le:
Round, s	slotted
Shaft Be	aring Type:
Bearing	
Actuator	Type:
Single sh	aft
Nonturn	Device Location:
At 3 oclo	ck and at 9 oclock
Nonturn	Device Radius:
0.531 inc	hes
Screw T	nread Diameter:
0.375 inc	hes
Screw T	nread Series Designator:
Unef	
Screw T	nready Qty Per Inch (tpi):
32.0	
Mountin	g Method:
Standard	bushing
Electrica	Il Resistance Per Section:
50.000 o	hms single section
Power D	issipation Rating Per Section In Watts:
2.0 free a	air single section

**Function Conformity Per Section:** 

Single section independent linearity

## NSN 5905-00-549-7453

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Resistance Tolerance Per Section In Percent:		
-10.0 to 10.0 single section		
Standard Taper Curve Per Section:		

A single section

**Terminal Type And Quantity:** 

3 tab, solder lug

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A002a0