## NSN 5905-00-549-8059

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-549-8059 **Section Quantity:** 2 First Flat Length: 0.500 inches Flat Height: 0.202 inches **Shaft Diameter:** 0.265 inches **Shaft Length:** Between 0.906 inches and 1.406 inches **Shaft Style:** Round, flatted **Actuator Type: Dual concentric Nonturn Device Location:** At 3 oclock and at 9 oclock **Nonturn Device Radius:** 0.531 inches **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Mounting Method:** Standard bushing **Electrical Resistance Per Section:** 500.000 kilohms 2nd section **Power Dissipation Rating Per Section In Watts:** 0.5 free air single section **Resistance Tolerance Per Section In Percent:** -20.0 to 20.0 2nd section **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:** 6 tab, solder lug Shelf Life: **Unit Of Measure:** 

N/a
Unit Of Measure:
-Demilitarization:

## NSN 5905-00-549-8059

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Fiig:

A002a0