

View Online at <https://aerobasegroup.com/nsn/5905-00-549-8735>

Section Quantity:

1

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

Terminal Length:

0.312 inches

First Flat Length:

0.500 inches

Flat Height:

0.218 inches

Body Diameter:

0.938 inches

Shaft Diameter:

Between 0.248 inches and 0.250 inches

Shaft Length:

0.938 inches

Mounting Bushing Length:

Any acceptable

Body Length:

0.453 inches

Overall Diameter:

1.250 inches

Shaft Style:

Round, flatted

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

300.0

Nonturn Device Location:

At 9 oclock

Nonturn Device Radius:

Between 0.422 inches and 0.453 inches

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Standard bushing w/shaft seal

Electrical Resistance Per Section:

50.000 kilohms single section

Rotary Actuator Travel In Angular Deg:

300.0

Power Dissipation Rating Per Section In Watts:

0.25 free air single section

Resistance Tolerance Per Section In Percent:

-20.0 to 20.0 single section

Actuator Travel Control Feature:

Stops

Standard Taper Curve Per Section:

V single section

Special Features:

0.375 in. Long bushing

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0