

View Online at https://aerobasegroup.com/nsn/5905-00-549-8745

# Section Quantity:

1

Body Style:

Cylindrical bushing mounted

# Reliability Indicator:

Not established

# **Body Diameter:**

1.094 inches

## Shaft Diameter:

0.250 inches

## Shaft Length:

2.500 inches

## Mounting Bushing Length:

0.375 inches

## Body Length:

# 0.609 inches

Shaft Style:

Round, slotted

## Shaft Bearing Type:

Sleeve

# **Contact Arm Electrical Off Position:**

Fully ccw

# Actuator Type:

Single shaft

# Effective Electrical Rotation In Deg Angular Rotation:

340.0

## **Maximum Starting Torque:**

6.00 inch-ounces

## Maximum Running Torque:

6.00 inch-ounces

## Maximum Stop Torque:

128.00 inch-ounces

## **Nonturn Device Location:**

At 9 oclock

## Nonturn Device Radius:

0.531 inches

## Fragility Factor:

Moderately rugged

# Screw Thread Diameter:

0.375 inches

## Screw Thread Series Designator:

Unef

# NSN 5905-00-549-8745

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Screw Thready Qty Per Inch (tpi):

32.0

## **Terminal Location:**

Radially positioned over less than half the circumference

## **Mounting Method:**

Standard bushing

# Cubic Measure:

0.528 cubic inches

## **Electrical Resistance Per Section:**

100.000 ohms single section

## **Rotary Actuator Travel In Angular Deg:**

340.0

## Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

120.0 single section

**Power Dissipation Rating Per Section In Watts:** 

2.0 free air single section

## **Resistance Tolerance Per Section In Percent:**

-10.0 to 10.0 single section

## Actuator Travel Control Feature:

## Stops

## Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

A single section

## **Test Data Document:**

81349-mil-r-94 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# Terminal Type And Quantity:

3 tab, solder lug

**Specification Data:** 

81349-mil-r-94/5 government specification

Shelf Life:

N/a

Unit Of Measure:

---

```
Demilitarization:
```

No

Fiig:

A002a0