Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-549-8747

### Section Quantity:

1

Body Style:

Cylindrical bushing mounted

# **Reliability Indicator:**

Not established

#### **Body Diameter:**

1.250 inches

#### Shaft Diameter:

0.375 inches

#### Shaft Length:

1.062 inches

#### Mounting Bushing Length:

1.000 inches

#### Body Length:

### 0.625 inches

Shaft Style:

#### Round

Actuator Type:

Single shaft

# Screw Thread Diameter:

0.250 inches

### Screw Thread Series Designator:

Unef

#### Screw Thready Qty Per Inch (tpi):

20.0

#### **Mounting Facility Quantity:**

3

#### Terminal Location:

Radially positioned over less than half the circumference

#### Mounting Method:

Threaded hole

#### **Features Provided:**

Nonmetallic shaft

#### **Electrical Resistance Per Section:**

25.000 kilohms single section

# Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

100.0 single section

# Power Dissipation Rating Per Section In Watts:

8.0 free air single section

### **Resistance Tolerance Per Section In Percent:**

-5.0 to 5.0 single section



## Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

40.0 single section

### Standard Taper Curve Per Section:

A single section

# Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

---

## Demilitarization:

No

#### Fiig:

A002a0