Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-549-9503

Section	Quantity:

1

Reliability Indicator:

Not established

First Flat Length:

0.188 inches

Flat Height:

0.156 inches

Shaft Diameter:

0.250 inches

Shaft Length:

0.688 inches

Shaft Style:

Round, flatted

Switch Type:

Rotary

Switch Voltage Rating In Volts:

125.0

Actuator Type:

Single shaft

Nonturn Device Location:

At 3 oclock and at 9 oclock

Nonturn Device Radius:

0.438 inches

Switch Operating Position:

Start of rotation

Switch Contact Arrangement:

Single pole, single throw, normally open, both positions maintained

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Mounting Method:

Standard bushing

Features Provided:

Switch

Electrical Resistance Per Section:

3.5 megohms single section

Power Dissipation Rating Per Section In Watts:

0.25 free air single section



Resistance Tolerance Per Section In Percent: -20.0 to 20.0 single section Switch Current Type And Rating In Amps: 3.000 ac/dc Standard Taper Curve Per Section: A single section Terminal Type And Quantity: 5 tab, solder lug Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A002a0