NSN 5905-00-551-1279

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-551-1279

Section Quantity:
1
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Body Diameter:
Between 1.062 inches and 1.250 inches
Shaft Length:
3.250 inches
Mounting Bushing Length:
0.375 inches
Body Length:
Between 0.500 inches and 0.625 inches
Shaft Style:
Round
Actuator Type:
Single shaft
Nonturn Device Location:
At 9 oclock
Nonturn Device Radius:
0.531 inches
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Mounting Method: Standard bushing
•
Standard bushing
Standard bushing Electrical Resistance Per Section:
Standard bushing Electrical Resistance Per Section: 20.0 ohms single section
Standard bushing Electrical Resistance Per Section: 20.0 ohms single section Power Dissipation Rating Per Section In Watts:
Standard bushing Electrical Resistance Per Section: 20.0 ohms single section Power Dissipation Rating Per Section In Watts: 2.0 free air single section
Standard bushing Electrical Resistance Per Section: 20.0 ohms single section Power Dissipation Rating Per Section In Watts: 2.0 free air single section Resistance Tolerance Per Section In Percent:

Terminal Type And Quantity:

3 tab, solder lug

NSN 5905-00-551-1279

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A002a0