NSN 5905-00-552-2097

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-552-2097

Section Quantity:
1
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Body Diameter:
2.250 inches
Shaft Diameter:
0.250 inches
Shaft Length:
0.500 inches
Mounting Bushing Length:
0.375 inches
Body Length:
1.375 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
Effective Electrical Rotation In Deg Angular Rotation: 300.0
300.0
300.0 Nonturn Device Location:
300.0 Nonturn Device Location: At 12 oclock
300.0 Nonturn Device Location: At 12 oclock Nonturn Device Radius:
300.0 Nonturn Device Location: At 12 oclock Nonturn Device Radius: Between 0.485 inches and 0.515 inches
300.0 Nonturn Device Location: At 12 oclock Nonturn Device Radius: Between 0.485 inches and 0.515 inches Screw Thread Diameter:
300.0 Nonturn Device Location: At 12 oclock Nonturn Device Radius: Between 0.485 inches and 0.515 inches Screw Thread Diameter: 0.375 inches
300.0 Nonturn Device Location: At 12 oclock Nonturn Device Radius: Between 0.485 inches and 0.515 inches Screw Thread Diameter: 0.375 inches Screw Thread Series Designator:
300.0 Nonturn Device Location: At 12 oclock Nonturn Device Radius: Between 0.485 inches and 0.515 inches Screw Thread Diameter: 0.375 inches Screw Thread Series Designator: Unef
Nonturn Device Location: At 12 oclock Nonturn Device Radius: Between 0.485 inches and 0.515 inches Screw Thread Diameter: 0.375 inches Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi):
Nonturn Device Location: At 12 oclock Nonturn Device Radius: Between 0.485 inches and 0.515 inches Screw Thread Diameter: 0.375 inches Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): 32.0
Nonturn Device Location: At 12 oclock Nonturn Device Radius: Between 0.485 inches and 0.515 inches Screw Thread Diameter: 0.375 inches Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): 32.0 Terminal Location:
Nonturn Device Location: At 12 oclock Nonturn Device Radius: Between 0.485 inches and 0.515 inches Screw Thread Diameter: 0.375 inches Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): 32.0 Terminal Location: Radially positioned over less than half the circumference
Nonturn Device Location: At 12 oclock Nonturn Device Radius: Between 0.485 inches and 0.515 inches Screw Thread Diameter: 0.375 inches Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): 32.0 Terminal Location: Radially positioned over less than half the circumference Mounting Method:
Nonturn Device Location: At 12 oclock Nonturn Device Radius: Between 0.485 inches and 0.515 inches Screw Thread Diameter: 0.375 inches Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): 32.0 Terminal Location: Radially positioned over less than half the circumference Mounting Method: Standard bushing
Nonturn Device Location: At 12 oclock Nonturn Device Radius: Between 0.485 inches and 0.515 inches Screw Thread Diameter: 0.375 inches Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): 32.0 Terminal Location: Radially positioned over less than half the circumference Mounting Method: Standard bushing Electrical Resistance Per Section:

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

340.0 single section

NSN 5905-00-552-2097

Fiig: A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Power Dissipation Rating Per Section In Watts:
50.0 free air single section
Resistance Tolerance Per Section In Percent:
-10.0 to 10.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No