NSN 5905-00-552-2265

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-552-2265

Section Quantity:
1
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Overall Length:
Between 1.302 inches and 1.562 inches
Terminal Length:
0.359 inches
Body Diameter:
Between 1.032 inches and 1.156 inches
Shaft Diameter:
Between 0.248 inches and 0.251 inches
Shaft Length:
Between 0.844 inches and 0.906 inches
Mounting Bushing Length:
Between 0.344 inches and 0.390 inches
Body Length:
Between 0.468 inches and 0.656 inches
Overall Diameter:
1.515 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Maximum Starting Torque:
6.00 inch-ounces
Maximum Stop Torque:
128.00 inch-ounces
Nonturn Device Location:
At 9 oclock
Nonturn Device Radius:
Between 0.515 inches and 0.547 inches
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0

Terminal Location:

Radially positioned over less than half the circumference

NSN 5905-00-552-2265

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Mounting Method:
Standard bushing
Electrical Resistance Per Section:
1.0 megohms single section
Rotary Actuator Travel In Angular Deg:
Between 309.0 and 320.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
120.0 single section
Power Dissipation Rating Per Section In Watts:
2.0 free air single section
Resistance Tolerance Per Section In Percent:
10.0 to 10.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
A single section
Test Data Document:
31349-mil-r-94 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Ferminal Type And Quantity:
3 tab, solder lug
Specification Data:
31349-mil-r-94/5 government specification
Shelf Life:
N/a
Jnit Of Measure:
-
Demilitarization:
No
Filg:
A002a0