

View Online at <https://aerobasegroup.com/nsn/5905-00-552-3112>

Section Quantity:

4

Body Style:

Cylindrical servo mounted

Reliability Indicator:

Not established

Pilot Diameter:

0.7497 inches

Pilot Length:

0.0650 inches

Overall Length:

2.820 inches

Undercut Diameter:

0.749 inches

Undercut Width:

0.0650 inches

Body Diameter:

0.883 inches

Shaft Diameter:

0.125 inches

Shaft Length:

0.470 inches

Body Length:

2.330 inches

Overall Diameter:

1.085 inches

Mounting Lip Diameter:

0.8830 inches

Mounting Lip Depth:

0.0650 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

340.0

Maximum Starting Torque:

0.40 inch-ounces

Maximum Running Torque:

0.40 inch-ounces

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Clamp ring

Electrical Resistance Per Section:

5.680 percent, rated amperes c and better industrial clears

Rotary Actuator Travel In Angular Deg:

360.0

Function Conformity Tolerance Per Section:

-0.30/+0.30 all sections

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

85.0 all sections

Power Dissipation Rating Per Section In Watts:

0.5 7th secondary switch

Function Conformity Per Section:

All sections independent linearity

Resistance Tolerance Per Section In Percent:

-4.0/+4.0 3rd section

Actuator Travel Control Feature:

Continuous motion

Function Characteristic Per Section:

All sections linear

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

25.0 all sections

Terminal Type And Quantity:

12 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0