NSN 5905-00-552-3268

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-552-3268

Section Quantity:
1
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Body Diameter:
1.620 inches
Shaft Diameter:
0.250 inches
Shaft Length:
0.430 inches
Mounting Bushing Length:
0.380 inches
Body Length:
0.560 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Nonturn Device Location:
At 3 oclock and at 9 oclock
Nonturn Device Radius:
1.190 inches
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
3.000 kilohms single section
Power Dissipation Rating Per Section In Watts:
4.0 free air single section
Resistance Tolerance Per Section In Percent:
-2.0 to 2.0 single section

A single section

Standard Taper Curve Per Section:

NSN 5905-00-552-3268

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Terminal	Type	And	Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0