

View Online at https://aerobasegroup.com/nsn/5905-00-552-3827

# Section Quantity: 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** Between 0.937 inches and 1.187 inches **Body Diameter:** Between 1.032 inches and 1.156 inches Shaft Diameter: Between 0.248 inches and 0.251 inches Shaft Length: Between 0.469 inches and 0.531 inches Mounting Bushing Length: Between 0.344 inches and 0.390 inches **Body Length:** Between 0.468 inches and 0.656 inches **Overall Diameter:** 1.515 inches Shaft Style: Round, slotted Actuator Type: Single shaft **Maximum Starting Torque:** 6.00 inch-ounces Maximum Stop Torque: 128.00 inch-ounces **Nonturn Device Location:** At 9 oclock **Nonturn Device Radius:** Between 0.515 inches and 0.547 inches Screw Thread Diameter: 0.375 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Radially positioned over less than half the circumference **Mounting Method:**

Standard bushing

# NSN 5905-00-552-3827

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



#### **Electrical Resistance Per Section:**

10.0 kilohms single section

# **Rotary Actuator Travel In Angular Deg:**

Between 309.0 and 320.0

# Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

120.0 single section

**Power Dissipation Rating Per Section In Watts:** 

1.0 free air single section

**Resistance Tolerance Per Section In Percent:** 

-10.0 to 10.0 single section

# **Actuator Travel Control Feature:**

#### Stops

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

C single section

# **Test Data Document:**

81349-mil-r-94 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# **Terminal Type And Quantity:**

3 tab, solder lug

Specification Data:

81349-mil-r-94/5 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0