NSN 5905-00-552-5034

Film Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-552-5034

Electrical Resistance: 26.700 kilohms Resistance Tolerance In Percent: 1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Immurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+150.0 Inclosure Method: Encapsulated Iterminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.375 inches Body Length: 1.062 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator:
Resistance Tolerance In Percent: 1.1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.375 inches Body Length: 1.002 inches Power Dissipation Rating In Watts: 1.000 free air
Resistance Tolerance In Percent: 1.1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.375 inches Body Length: 1.062 inches Power Dissipation Rating In Watts: 1.000 free air
Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 155.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.375 inches Body Length: 1.062 inches Power Dissipation Rating In Watts: 1.000 free air
Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 155.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 10.375 inches Body Length: 1.062 inches Power Dissipation Rating In Watts: 1.000 free air
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 155.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.375 inches Body Length: 1.062 inches Power Dissipation Rating In Watts: 1.000 free air
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 155.0/+150.0 Inclosure Method: Incapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 10.375 inches Body Length: 1.062 inches Power Dissipation Rating In Watts: 1.000 free air
Informer Range Of Tempurature Coefficient In Deg Celsius: 155.0/+150.0 Inclosure Method: Encapsulated Iterminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 10.375 inches Body Length: 1.062 inches Power Dissipation Rating In Watts: 1.000 free air
Fempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+150.0 Inclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.375 inches Body Length: 1.062 inches Power Dissipation Rating In Watts: 1.000 free air
inclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.375 inches Body Length: 1.062 inches Power Dissipation Rating In Watts: 1.000 free air
Inclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.375 inches Body Length: 1.062 inches Power Dissipation Rating In Watts: 1.000 free air
Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.375 inches Body Length: 1.062 inches Power Dissipation Rating In Watts: 1.000 free air
Ferminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.375 inches Body Length: 1.062 inches Power Dissipation Rating In Watts: 1.000 free air
Wire lead Reliability Indicator: Not established Body Diameter: 0.375 inches Body Length: 1.062 inches Power Dissipation Rating In Watts: 1.000 free air
Reliability Indicator: Not established Body Diameter: 0.375 inches Body Length: 1.062 inches Power Dissipation Rating In Watts: 1.000 free air
Not established Body Diameter: 0.375 inches Body Length: 1.062 inches Power Dissipation Rating In Watts: 1.000 free air
Body Diameter: 0.375 inches Body Length: 1.062 inches Power Dissipation Rating In Watts: 1.000 free air
0.375 inches Body Length: 1.062 inches Power Dissipation Rating In Watts: 1.000 free air
Body Length: 1.062 inches Power Dissipation Rating In Watts: 1.000 free air
1.062 inches Power Dissipation Rating In Watts: 1.000 free air
Power Dissipation Rating In Watts: 1.000 free air
1.000 free air
Style Designator:
Axial terminal each end
Test Data Document:
31349-mil-r-10509 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
31349-mil-r-10509/5 government specification
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Filg:
A001a0