## NSN 5905-00-552-5882

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-552-5882

| Section Quantity:   |
|---|
| 1   |
| Body Style:   |
| Cylindrical bushing mounted   |
| Reliability Indicator:  |
| Not established   |
| First Flat Length:  |
| 0.375 inches  |
| Flat Height:  |
| 0.216 inches  |
| Body Diameter:  |
| 1.280 inches  |
| Shaft Diameter:   |
| 0.250 inches  |
| Shaft Length:   |
| 0.750 inches  |
| Mounting Bushing Length:  |
| 0.250 inches  |
| Body Length:  |
| 0.620 inches  |
| Overall Diameter:   |
| 1.640 inches  |
| Shaft Style:  |
| Round, flatted  |
| Actuator Type:  |
| Single shaft  |
| Screw Thread Diameter:  |
| 0.375 inches  |
| Screw Thread Series Designator:   |
| Unef  |
| Screw Thready Qty Per Inch (tpi):   |
| 32.0  |
| Terminal Location:  |
| Radially positioned over less than half the circumference                   |
| Mounting Method:  |
| Standard bushing  |
| Electrical Resistance Per Section:  |
| 5.000 kilohms single section  |
| Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: |
| 105.0 single section  |
| Power Dissipation Rating Per Section In Watts:                              |

2.0 free air single section

## NSN 5905-00-552-5882

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



-10.0 to 10.0 single section

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

40.0 single section

**Standard Taper Curve Per Section:** 

A single section

**Terminal Type And Quantity:** 

3 tab, solder lug

.

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A002a0