

View Online at <https://aerobasegroup.com/nsn/5905-00-552-5904>

**Section Quantity:**

1

**Body Style:**

Cylindrical bushing mounted

**First Flat Length:**

0.344 inches

**Flat Height:**

0.219 inches

**Body Diameter:**

1.562 inches

**Shaft Diameter:**

0.250 inches

**Shaft Length:**

1.000 inches

**Mounting Bushing Length:**

0.375 inches

**Body Length:**

1.375 inches

**Shaft Style:**

Round, flatted

**Contact Arm Electrical Off Position:**

Fully ccw

**Actuator Type:**

Single shaft

**Nonturn Device Location:**

At 12 oclock

**Nonturn Device Radius:**

0.500 inches

**Screw Thread Diameter:**

0.375 inches

**Screw Thread Series Designator:**

Unef

**Screw Thready Qty Per Inch (tpi):**

32.0

**Mounting Method:**

Standard bushing

**Electrical Resistance Per Section:**

40.000 ohms single section

**Power Dissipation Rating Per Section In Watts:**

25.0 free air single section

**Resistance Tolerance Per Section In Percent:**

-10.0 to 10.0 single section

**Standard Taper Curve Per Section:**

A single section

**Terminal Type And Quantity:**

2 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A002a0