NSN 5905-00-552-6622

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-552-6622 **Section Quantity:** 1 **Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** 0.7500 inches Pilot Length: 0.0620 inches **Overall Length:** 1.270 inches **Undercut Diameter:** 0.781 inches **Undercut Width:** 0.0620 inches **Body Diameter:** 0.875 inches **Shaft Diameter:** Between 0.1245 inches and 0.1248 inches **Shaft Length:** 0.500 inches **Body Length:** 0.770 inches **Overall Diameter:** 1.032 inches **Mounting Lip Diameter:** 0.8750 inches **Mounting Lip Depth:** 0.0620 inches **Shaft Style:** Round **Shaft Bearing Type:** Ball **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 354.0 **Maximum Starting Torque:**

0.10 inch-ounces

Maximum Running Torque:

0.10 inch-ounces

NSN 5905-00-552-6622

Precision Wire Wound Variable Resistor - Page 2 of 3



Shaft End Play:
0.00400 inches
Shaft Runout:
0.001 inches
Lateral Runout:
0.002 inches
Pilot Diameter Runout:
0.00150 inches
Shaft Radial Play:
0.002 inches
Fragility Factor:
Moderately delicate
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Clamp ring
Electrical Resistance Per Section:
10.000 percent, rated amperes c and better flooring
Rotary Actuator Travel In Angular Deg:
360.0
Function Conformity Tolerance Per Section:
-0.50/+0.50 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 single section
Power Dissipation Rating Per Section In Watts:
1.25 7th secondary quality
Function Conformity Per Section:
Single section independent linearity
Fixed Tap Quantity Per Section:
1 single section
Tap Location Tolerance Per Section:
-5.0/+5.0 ohms single section
Resistance Tolerance Per Section In Percent:
-5.0/+5.0 single section
Actuator Travel Control Feature:
Continuous motion
Tap Location From Ccw Terminal Per Section In Ohms:
5000.0 single section
Function Characteristic Per Section:
7 oclock all primaries
Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:

70.0 single section

-20.0/+20.0 single section

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

NSN 5905-00-552-6622

Precision Wire Wound Variable Resistor - Page 3 of 3



Terminal Type And Quantity:
4 turret
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A002a0