## NSN 5905-00-553-9107



	onprecision Nonwire Wound Variable Resistor - Page 1 of 2
Vie	w Online at https://aerobasegroup.com/nsn/5905-00-553-9107
Se	ction Quantity:
1	
Во	dy Style:
Су	indrical bushing mounted
Re	liability Indicator:
No	t established
Ov	erall Length:
Be	ween 1.312 inches and 1.562 inches
Во	dy Diameter:
Be	ween 1.032 inches and 1.156 inches
Sh	aft Diameter:
Be	ween 0.248 inches and 0.251 inches
Sh	aft Length:
Be	ween 0.844 inches and 0.906 inches
Мо	unting Bushing Length:
Be	ween 0.344 inches and 0.390 inches
Во	dy Length:
Be	ween 0.468 inches and 0.656 inches
Ov	erall Diameter:
1.5	15 inches
Sh	aft Style:
Ro	und, slotted
Ac	tuator Type:
Sir	gle shaft
Ма	ximum Starting Torque:
6.0	0 inch-ounces
Ма	ximum Stop Torque:
129	3.00 inch-ounces

128.00 inch-ounces

**Nonturn Device Location:** 

At 9 oclock

**Nonturn Device Radius:** 

Between 0.515 inches and 0.547 inches

**Screw Thread Diameter:** 

0.375 inches

**Screw Thread Series Designator:** 

Unef

Screw Thready Qty Per Inch (tpi):

32.0

**Terminal Location:** 

Radially positioned over less than half the circumference

**Mounting Method:** 

Standard bushing

## NSN 5905-00-553-9107

A002a0

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Electrical Resistance Per Section:
750.0 ohms single section
Rotary Actuator Travel In Angular Deg:
Between 309.0 and 320.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
120.0 single section
Power Dissipation Rating Per Section In Watts:
2.0 free air single section
Resistance Tolerance Per Section In Percent:
-10.0 to 10.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
A single section
Test Data Document:
81349-mil-r-94 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification formation
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
3 tab, solder lug
Specification Data:
81349-mil-r-94/5 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: