

View Online at <https://aerobasegroup.com/nsn/5905-00-553-9217>

Section Quantity:

3

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

First Flat Length:

0.344 inches

Flat Height:

0.219 inches

Body Diameter:

2.312 inches

Shaft Diameter:

0.250 inches

Shaft Length:

Between 0.844 inches and 0.906 inches

Mounting Bushing Length:

0.375 inches

Body Length:

5.500 inches

Shaft Style:

Round, flatted

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

300.0

Nonturn Device Location:

At 6 oclock

Nonturn Device Radius:

0.500 inches

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef

Screw Thread Qty Per Inch (tpi):

32.0

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Standard bushing

Electrical Resistance Per Section:

12.000 ohms all sections

Rotary Actuator Travel In Angular Deg:

300.0

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

340.0 all sections

Power Dissipation Rating Per Section In Watts:

50.0 free air all sections

Resistance Tolerance Per Section In Percent:

-10.0 to 10.0 all sections

Actuator Travel Control Feature:

Stops

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

40.0 all sections

Standard Taper Curve Per Section:

A all sections

Terminal Type And Quantity:

9 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0