NSN 5905-00-553-9369

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-553-9369 **Section Quantity:** 1 **Body Style:** Rectangular w/mounting holes/slots **Reliability Indicator:** Not established **Overall Length:** 1.438 inches **Overall Height:** 0.312 inches **Overall Width:** 0.250 inches **Mounting Hole Diameter:** 0.086 inches **Shaft Diameter:** 0.125 inches **Shaft Length:** 0.188 inches **Body Length:** 1.250 inches **Body Width:** 0.250 inches **Body Height:** 0.312 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Maximum Starting Torque:** 7.50 inch-ounces **Lateral Distance Between Mounting Hole Centers:** 1.000 inches **Mounting Facility Quantity:** 2 **Terminal Location:** Rear end **Mounting Method:**

Unthreaded hole **Features Provided:** Nonmetallic shaft

Electrical Resistance Per Section:

100.000 ohms single section

NSN 5905-00-553-9369

Fiig: A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Rotary Actuator Travel In Angular Deg:
9000.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
175.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-50.0 to 50.0 single section
Power Dissipation Rating Per Section In Watts:
1.0 free air single section
Resistance Tolerance Per Section In Percent:
-10.0 to 10.0 single section
Actuator Travel Control Feature:
Clutch
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 wire lead
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No