## NSN 5905-00-553-9942



View C	Online at https://aerobasegroup.com/nsn/5905-00-553-9942
Sectio	n Quantity:
1	
Body \$	Style:
Cylindr	ical bushing mounted
Reliab	ility Indicator:
Not es	tablished
Overal	I Length:
Betwee	en 2.937 inches and 3.187 inches
Body I	Diameter:
Betwee	en 1.032 inches and 1.156 inches
Shaft I	Diameter:
Betwee	en 0.248 inches and 0.251 inches
Shaft I	_ength:
Betwee	en 2.469 inches and 2.531 inches
Mount	ing Bushing Length:
Betwee	en 0.344 inches and 0.390 inches
Body I	_ength:
Betwee	en 0.468 inches and 0.656 inches
Overal	I Diameter:
1.515 i	nches
Shaft S	Style:
Round	, slotted
Actuat	or Type:
Single	shaft
Maxim	um Starting Torque:
6 00 in	ch-ounces

128.00 inch-ounces

**Nonturn Device Location:** 

At 9 oclock

**Nonturn Device Radius:** 

Between 0.515 inches and 0.547 inches

**Screw Thread Diameter:** 

0.375 inches

**Screw Thread Series Designator:** 

Unef

Screw Thready Qty Per Inch (tpi):

32.0

**Terminal Location:** 

Radially positioned over less than half the circumference

**Mounting Method:** 

Standard bushing

## NSN 5905-00-553-9942

**Fiig:** A002a0

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Electrical Resistance Per Section:
100.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
Between 309.0 and 320.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
120.0 single section
Power Dissipation Rating Per Section In Watts:
1.0 free air single section
Resistance Tolerance Per Section In Percent:
-10.0 to 10.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
C single section
Test Data Document:
81349-mil-r-94 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format;
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
3 tab, solder lug
Specification Data:
81349-mil-r-94/5 government specification
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No