NSN 5905-00-554-8557

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-554-8557 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length: 3.143** inches **Body Diameter:** 1.062 inches **Shaft Diameter:** 0.125 inches **Shaft Length:** 2.125 inches **Mounting Bushing Length:** 0.250 inches **Body Length:** 0.768 inches **Overall Diameter:** 1.624 inches **Shaft Style:** Round, slotted Switch Type: Rotary **Switch Voltage Rating In Volts:** 125.0 **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 315.0 **Nonturn Device Location:** At 3 oclock and at 9 oclock **Nonturn Device Radius:** 0.531 inches **Switch Operating Position:** Start of rotation **Switch Contact Arrangement:** Single pole, single throw, normally open, both positions maintained **Fragility Factor:** Moderately delicate

Screw Thread Diameter: 0.375 inches

NSN 5905-00-554-8557

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Screw Thread Series Designator:
Jnef Control of the C
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Standard bushing
Features Provided:
Switch
Electrical Resistance Per Section:
25.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
315.0
Resistance Tempurature Characteristic Range Per Section In Percent:
3.0 to 0.0 -55 degrees celsius single section and -5.0 to 10.0 -25 degrees celsius single section and -5.0 to 10.0 25 degrees celsius single
section and +0.0 to 3.0 120 degrees celsius single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
120.0 single section
Power Dissipation Rating Per Section In Watts:
2.0 free air single section
Resistance Tolerance Per Section In Percent:
20.0 to 20.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Switch Current Type And Rating In Amps:
3.000 ac
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
5 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Filg:
A002a0