NSN 5905-00-556-3042



View Online at	https://aerobasegroup.com/nsn/5905-00-556-3042
Section Quant	tity:
1	
Body Style:	
Cylindrical bus	hing mounted
Reliability Ind	icator:
Not established	i de la companya de
Overall Lengtl	h:
Between 1.312	inches and 1.562 inches
Body Diamete	r:
Between 1.032	inches and 1.150 inches
Shaft Diamete	r:
Between 0.248	inches and 0.251 inches
Shaft Length:	
Between 0.844	inches and 0.906 inches
Mounting Bus	hing Length:
Between 0.485	inches and 0.515 inches
Body Length:	
Between 0.468	inches and 0.656 inches
Overall Diame	ter:
1.515 inches	
Shaft Style:	
Round, slotted	l .
Actuator Type	:
Single shaft	
Maximum Sta	rting Torque:
6.00 inch-ounc	es
Maximum Sto	p Torque:
128.00 inch-ou	nces

Nonturn Device Location:

At 9 oclock

Nonturn Device Radius:

Between 0.515 inches and 0.547 inches

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Locking bushing

NSN 5905-00-556-3042

Fiig: A002a0

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Electrical Resistance Per Section:
100.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
Between 309.0 and 320.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
120.0 single section
Power Dissipation Rating Per Section In Watts:
2.0 free air single section
Resistance Tolerance Per Section In Percent:
-10.0 to 10.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
A single section
Test Data Document:
81349-mil-r-94 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification formation
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
3 tab, solder lug
Specification Data:
81349-mil-r-94/5 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No