## NSN 5905-00-556-3351



Section Quantity:  1 Body Style: Cylindrical bushing mounted Reliability Indicator: Not established Overall Length: Between 1.312 inches and 1.562 inches Body Diameter: Between 1.032 inches and 1.156 inches Shaft Diameter: Between 0.248 inches and 0.251 inches Shaft Length: Between 0.844 inches and 0.906 inches Mounting Bushing Length: Between 0.344 inches and 0.390 inches Body Length: Between 0.468 inches and 0.656 inches Overall Diameter: 1.515 inches Shaft Style: Round, slotted Actuator Type: Single shaft Maximum Starting Torque: 6.00 inch-ounces Maximum Stop Torque:	View Online at I	nttps://aerobasegroup.com/nsn/5905-00-556-3351
Body Style: Cylindrical bushing mounted Reliability Indicator: Not established Overall Length: Between 1.312 inches and 1.562 inches Body Diameter: Between 1.032 inches and 1.156 inches Shaft Diameter: Between 0.248 inches and 0.251 inches Shaft Length: Between 0.844 inches and 0.906 inches Mounting Bushing Length: Between 0.344 inches and 0.390 inches Body Length: Between 0.468 inches and 0.656 inches Overall Diameter: 1.515 inches Shaft Style: Round, slotted Actuator Type: Single shaft Maximum Starting Torque: 6.00 inch-ounces	Section Quant	ity:
Cylindrical bushing mounted  Reliability Indicator:  Not established  Overall Length:  Between 1.312 inches and 1.562 inches  Body Diameter:  Between 1.032 inches and 1.156 inches  Shaft Diameter:  Between 0.248 inches and 0.251 inches  Shaft Length:  Between 0.844 inches and 0.906 inches  Mounting Bushing Length:  Between 0.344 inches and 0.390 inches  Body Length:  Between 0.468 inches and 0.656 inches  Overall Diameter:  1.515 inches  Shaft Style:  Round, slotted  Actuator Type:  Single shaft  Maximum Starting Torque:  6.00 inch-ounces	1	
Reliability Indicator: Not established Overall Length: Between 1.312 inches and 1.562 inches Body Diameter: Between 1.032 inches and 1.156 inches Shaft Diameter: Between 0.248 inches and 0.251 inches Shaft Length: Between 0.844 inches and 0.906 inches Mounting Bushing Length: Between 0.344 inches and 0.390 inches Body Length: Between 0.468 inches and 0.656 inches Overall Diameter: 1.515 inches Shaft Style: Round, slotted Actuator Type: Single shaft Maximum Starting Torque: 6.00 inch-ounces	Body Style:	
Not established  Overall Length: Between 1.312 inches and 1.562 inches  Body Diameter: Between 1.032 inches and 1.156 inches  Shaft Diameter: Between 0.248 inches and 0.251 inches  Shaft Length: Between 0.844 inches and 0.906 inches  Mounting Bushing Length: Between 0.344 inches and 0.390 inches  Body Length: Between 0.468 inches and 0.656 inches  Overall Diameter: 1.515 inches  Shaft Style: Round, slotted  Actuator Type: Single shaft  Maximum Starting Torque: 6.00 inch-ounces	Cylindrical bush	ning mounted
Overall Length: Between 1.312 inches and 1.562 inches  Body Diameter: Between 1.032 inches and 1.156 inches  Shaft Diameter: Between 0.248 inches and 0.251 inches  Shaft Length: Between 0.844 inches and 0.906 inches  Mounting Bushing Length: Between 0.344 inches and 0.390 inches  Body Length: Between 0.468 inches and 0.656 inches  Overall Diameter: 1.515 inches  Shaft Style: Round, slotted  Actuator Type: Single shaft  Maximum Starting Torque: 6.00 inch-ounces	Reliability Indi	cator:
Between 1.312 inches and 1.562 inches  Body Diameter:  Between 1.032 inches and 1.156 inches  Shaft Diameter:  Between 0.248 inches and 0.251 inches  Shaft Length:  Between 0.844 inches and 0.906 inches  Mounting Bushing Length:  Between 0.344 inches and 0.390 inches  Body Length:  Between 0.468 inches and 0.656 inches  Overall Diameter:  1.515 inches  Shaft Style:  Round, slotted  Actuator Type:  Single shaft  Maximum Starting Torque:  6.00 inch-ounces	Not established	
Between 1.032 inches and 1.156 inches Shaft Diameter: Between 0.248 inches and 0.251 inches Shaft Length: Between 0.844 inches and 0.906 inches Mounting Bushing Length: Between 0.344 inches and 0.390 inches Body Length: Between 0.468 inches and 0.656 inches Overall Diameter: 1.515 inches Shaft Style: Round, slotted Actuator Type: Single shaft Maximum Starting Torque: 6.00 inch-ounces	Overall Length	:
Between 1.032 inches and 1.156 inches  Shaft Diameter:  Between 0.248 inches and 0.251 inches  Shaft Length:  Between 0.844 inches and 0.906 inches  Mounting Bushing Length:  Between 0.344 inches and 0.390 inches  Body Length:  Between 0.468 inches and 0.656 inches  Overall Diameter:  1.515 inches  Shaft Style:  Round, slotted  Actuator Type:  Single shaft  Maximum Starting Torque:  6.00 inch-ounces	Between 1.312	inches and 1.562 inches
Shaft Diameter: Between 0.248 inches and 0.251 inches  Shaft Length: Between 0.844 inches and 0.906 inches  Mounting Bushing Length: Between 0.344 inches and 0.390 inches  Body Length: Between 0.468 inches and 0.656 inches  Overall Diameter: 1.515 inches  Shaft Style: Round, slotted  Actuator Type: Single shaft  Maximum Starting Torque: 6.00 inch-ounces	Body Diameter	:
Between 0.248 inches and 0.251 inches  Shaft Length:  Between 0.844 inches and 0.906 inches  Mounting Bushing Length:  Between 0.344 inches and 0.390 inches  Body Length:  Between 0.468 inches and 0.656 inches  Overall Diameter:  1.515 inches  Shaft Style:  Round, slotted  Actuator Type:  Single shaft  Maximum Starting Torque:  6.00 inch-ounces	Between 1.032	inches and 1.156 inches
Shaft Length: Between 0.844 inches and 0.906 inches  Mounting Bushing Length: Between 0.344 inches and 0.390 inches  Body Length: Between 0.468 inches and 0.656 inches  Overall Diameter: 1.515 inches  Shaft Style: Round, slotted  Actuator Type: Single shaft  Maximum Starting Torque: 6.00 inch-ounces	Shaft Diameter	:
Between 0.844 inches and 0.906 inches  Mounting Bushing Length:  Between 0.344 inches and 0.390 inches  Body Length:  Between 0.468 inches and 0.656 inches  Overall Diameter:  1.515 inches  Shaft Style:  Round, slotted  Actuator Type:  Single shaft  Maximum Starting Torque:  6.00 inch-ounces	Between 0.248	inches and 0.251 inches
Mounting Bushing Length: Between 0.344 inches and 0.390 inches  Body Length: Between 0.468 inches and 0.656 inches  Overall Diameter: 1.515 inches  Shaft Style: Round, slotted  Actuator Type: Single shaft  Maximum Starting Torque: 6.00 inch-ounces	Shaft Length:	
Between 0.344 inches and 0.390 inches  Body Length: Between 0.468 inches and 0.656 inches  Overall Diameter: 1.515 inches  Shaft Style: Round, slotted  Actuator Type: Single shaft  Maximum Starting Torque: 6.00 inch-ounces	Between 0.844	inches and 0.906 inches
Body Length: Between 0.468 inches and 0.656 inches  Overall Diameter:  1.515 inches  Shaft Style: Round, slotted  Actuator Type: Single shaft  Maximum Starting Torque: 6.00 inch-ounces	Mounting Busl	ning Length:
Between 0.468 inches and 0.656 inches  Overall Diameter:  1.515 inches  Shaft Style:  Round, slotted  Actuator Type:  Single shaft  Maximum Starting Torque:  6.00 inch-ounces	Between 0.344	inches and 0.390 inches
Overall Diameter:  1.515 inches  Shaft Style: Round, slotted  Actuator Type: Single shaft  Maximum Starting Torque:  6.00 inch-ounces	Body Length:	
1.515 inches  Shaft Style: Round, slotted  Actuator Type: Single shaft  Maximum Starting Torque: 6.00 inch-ounces	Between 0.468	inches and 0.656 inches
Shaft Style: Round, slotted Actuator Type: Single shaft Maximum Starting Torque: 6.00 inch-ounces	Overall Diamet	er:
Round, slotted  Actuator Type: Single shaft  Maximum Starting Torque: 6.00 inch-ounces	1.515 inches	
Actuator Type: Single shaft  Maximum Starting Torque: 6.00 inch-ounces	Shaft Style:	
Single shaft  Maximum Starting Torque: 6.00 inch-ounces	Round, slotted	
Maximum Starting Torque: 6.00 inch-ounces	Actuator Type:	
6.00 inch-ounces	Single shaft	
	Maximum Star	ting Torque:
Maximum Stop Torque:	6.00 inch-ounce	es
	Maximum Stop	Torque:

**Nonturn Device Location:** 

At 9 oclock

**Nonturn Device Radius:** 

Between 0.515 inches and 0.547 inches

**Screw Thread Diameter:** 

0.375 inches

**Screw Thread Series Designator:** 

Unef

Screw Thready Qty Per Inch (tpi):

32.0

**Terminal Location:** 

Radially positioned over less than half the circumference

**Mounting Method:** 

Standard bushing

## NSN 5905-00-556-3351

**Fiig:** A002a0

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Electrical Resistance Per Section:
75.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
Between 309.0 and 320.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
120.0 single section
Power Dissipation Rating Per Section In Watts:
1.0 free air single section
Resistance Tolerance Per Section In Percent:
-10.0 to 10.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
C single section
Test Data Document:
81349-mil-r-94 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format;
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
3 tab, solder lug
Specification Data:
81349-mil-r-94/5 government specification
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No