

View Online at <https://aerobasegroup.com/nsn/5905-00-556-4648>

Section Quantity:

2

Body Style:

Cylindrical servo mounted

Reliability Indicator:

Not established

Pilot Diameter:

0.7500 inches

Pilot Length:

0.0620 inches

Undercut Diameter:

1.820 inches

Undercut Width:

0.0620 inches

Body Diameter:

2.000 inches

Angle Of Mounting Hole In Deg:

90.0

Angle Between Centerlines Of Mounting Holes In Deg:

120.0

Shaft Diameter:

Between 0.2495 inches and 0.2500 inches

Shaft Length:

0.750 inches

Body Length:

3.531 inches

Mounting Lip Diameter:

1.8750 inches

Mounting Lip Depth:

0.0620 inches

Mounting Hole/stud Circle Diameter:

1.500 inches

Shaft Style:

Round

Shaft Bearing Type:

Bearing

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

3600.0

Maximum Starting Torque:

1.90 inch-ounces

Maximum Running Torque:

1.30 inch-ounces

Shaft End Play:

0.00500 inches

Shaft Runout:

0.005 inches

Lateral Runout:

0.002 inches

Pilot Diameter Runout:

0.00150 inches

Shaft Radial Play:

0.002 inches

Screw Thread Diameter:

0.164 inches

Screw Thread Series Designator:

Unc

Screw Thready Qty Per Inch (tpi):

32.0

Mounting Facility Quantity:

3

Terminal Location:

Longitudinally positioned on the circumference

Mounting Method:

Threaded hole

Features Provided:

Nonmetallic shaft

Electrical Resistance Per Section:

5.000 percent, rated amperes c and better finish

Tap Location From Ccw Terminal Per Section In Deg Of Effective Electrical Rotation:

2542.0 1st section

Rotary Actuator Travel In Angular Deg:

3600.0

Function Conformity Tolerance Per Section:

-0.10/+0.10 1st section

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

80.0 all sections

Power Dissipation Rating Per Section In Watts:

5.0 free air all sections

Function Conformity Per Section:

All sections independent linearity

Fixed Tap Quantity Per Section:

1 1st section

Tap Location Tolerance Per Section:

-5.0/+5.0 degrees angular rotation 1st section

Resistance Tolerance Per Section In Percent:

-5.0/+5.0 1st section

Actuator Travel Control Feature:

Stops

Function Characteristic Per Section:

All sections linear

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

40.0 all sections

Terminal Type And Quantity:

7 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0