Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-556-4769

## Section Quantity:

2

Body Style:

Cylindrical bushing mounted

## **Reliability Indicator:**

Not established

#### **Body Diameter:**

1.156 inches

#### Shaft Diameter:

0.250 inches

#### Shaft Length:

0.625 inches

Mounting Bushing Length:

#### 0.500 inches

Body Length:

### 1.266 inches

Shaft Style:

Round, slotted

#### Shaft Bearing Type:

Bearing

### Actuator Type:

Single shaft

### Nonturn Device Location:

At 3 oclock and at 9 oclock

### Nonturn Device Radius:

0.531 inches

#### Screw Thread Diameter:

0.375 inches

### Screw Thread Series Designator:

Unef

# Screw Thready Qty Per Inch (tpi):

32.0

## **Terminal Location:**

Radially positioned over less than half the circumference

## Mounting Method:

Standard bushing

## **Electrical Resistance Per Section:**

1.0 megohms all sections

# Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

120.0 all sections

## Power Dissipation Rating Per Section In Watts:

2.0 free air all sections



**Resistance Tolerance Per Section In Percent:** -20.0 to 20.0 all sections Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 all sections Standard Taper Curve Per Section: A all sections Terminal Type And Quantity: 6 tab, solder lug Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A002a0