Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-556-4988

view Online at https://defobasegroup.com/hsn/55	0.
Section Quantity:	
1	
Shaft Diameter:	
0.250 inches	
Shaft Length:	
0.438 inches	
Mounting Bushing Length:	
0.375 inches	
Shaft Style:	
Round, slotted	
Actuator Type:	
Single shaft	
Nonturn Device Location:	
At 9 oclock	
Nonturn Device Radius:	
0.234 inches	
Screw Thread Diameter:	
0.250 inches	
Screw Thread Series Designator:	
Unef	
Screw Thready Qty Per Inch (tpi):	
32.0	
Mounting Method:	
Locking bushing	
Features Provided:	
Nonmetallic shaft	
Electrical Resistance Per Section:	
10.000 kilohms single section	
Power Dissipation Rating Per Section In Watts	:
1.5 free air single section	
Resistance Tolerance Per Section In Percent:	
-5.0 to 5.0 single section	
Standard Taper Curve Per Section:	
A single section	
Terminal Type And Quantity:	
3 tab, solder lug	
Shelf Life:	
N/a	
Unit Of Measure:	
 Demilitarization:	
No	

NSN 5905-00-556-4988

Nonprecision Wire Wound Variable Resistor - Page 2 of 2

Fiig: A002a0

