Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-556-5193

### Section Quantity:

1

Body Style:

Cylindrical bushing mounted

## **Reliability Indicator:**

Not established

#### **Body Diameter:**

1.093 inches

#### Shaft Diameter:

0.250 inches

Shaft Length:

0.625 inches

Mounting Bushing Length:

#### 0.500 inches

Body Length:

## 0.562 inches

Shaft Style:

Round, slotted

#### Actuator Type:

Single shaft

### Nonturn Device Location:

At 9 oclock

### Nonturn Device Radius:

0.531 inches

#### Screw Thread Diameter:

0.375 inches

#### Screw Thread Series Designator:

Unef

### Screw Thready Qty Per Inch (tpi):

32.0

# **Terminal Location:**

Radially positioned over less than half the circumference

## **Mounting Method:**

Standard bushing

# **Electrical Resistance Per Section:**

50.000 kilohms single section

# Power Dissipation Rating Per Section In Watts:

2.0 free air single section

# **Resistance Tolerance Per Section In Percent:**

-20.0/+20.0 single section

# Terminal Type And Quantity:

3 tab, solder lug

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0