NSN 5905-00-556-6418

Film Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-556-6418

| Electrical Resistance: 1.500 kilohms Resistance Tolerance In Percent: 1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 155.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: |
|--|
| Resistance Tolerance In Percent: -1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: -70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: -150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+150.0 Inclosure Method: |
| Resistance Tolerance In Percent: -1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: -70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: -150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+150.0 Inclosure Method: |
| Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 150.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: |
| Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: |
| Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 155.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: |
| Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 155.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: |
| Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: |
| Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: |
| nclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: |
| Inclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: |
| Encapsulated Terminal Type: Wire lead Reliability Indicator: |
| Ferminal Type: Wire lead Reliability Indicator: |
| Wire lead Reliability Indicator: |
| Reliability Indicator: |
| |
| |
| Not established |
| Body Diameter: |
| 0.375 inches |
| Body Length: |
| 2.187 inches |
| Power Dissipation Rating In Watts: |
| 2.000 free air |
| Style Designator: |
| Axial terminal each end |
| Test Data Document: |
| 31349-mil-r-10509 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Specification Data: |
| 31349-mil-r-10509/6 government specification |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| - |
| Demilitarization: |
| No |
| Fiig: |
| A001a0 |