NSN 5905-00-556-6564

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-556-6564 **Section Quantity:** 1 **Body Style:** Cylindrical studs mounted **Reliability Indicator:** Not established **Body Diameter:** 2.750 inches **Shaft Diameter:** 0.375 inches **Shaft Length:** 1.000 inches **Body Length:** 1.125 inches **Mounting Hole/stud Circle Diameter:** 0.875 inches **Shaft Style:** Round **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 320.0 **Screw Thread Diameter:** 0.138 inches **Screw Thread Series Designator:** Unc Screw Thready Qty Per Inch (tpi): 32.0 **Mounting Facility Quantity:** 3 **Terminal Location:** Radially positioned over less than half the circumference **Mounting Method:** Threaded hole **Features Provided:** Nonmetallic shaft

Electrical Resistance Per Section:

30.000 kilohms single section

Rotary Actuator Travel In Angular Deg:

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

100.0 single section

NSN 5905-00-556-6564

Fiig: A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -200.0 to 200.0 single section **Power Dissipation Rating Per Section In Watts:** 10.0 free air single section **Resistance Tolerance Per Section In Percent:** -2.0 to 2.0 single section **Actuator Travel Control Feature:** Stops Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 25.0 single section **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:** 3 tab, solder lug Shelf Life: N/a **Unit Of Measure: Demilitarization:** No