NSN 5905-00-556-6565

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-556-6565

Section Quantity:
1
Body Style:
Cylindrical studs mounted
Reliability Indicator:
Not established
Body Diameter:
2.750 inches
Shaft Diameter:
0.375 inches
Shaft Length:
0.875 inches
Body Length:
1.120 inches
Mounting Hole/stud Circle Diameter:
2.000 inches
Shaft Style:
Round
Actuator Type:
Double ended shaft
Effective Electrical Rotation In Deg Angular Rotation:
360.0
Screw Thread Diameter:
0.138 inches
Screw Thread Series Designator:
Unc
Screw Thready Qty Per Inch (tpi):
32.0
Mounting Facility Quantity:
3
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Threaded hole
Electrical Resistance Per Section:
5.000 kilohms single section
Rotary Actuator Travel In Angular Deg:
360.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
100.0 single section
Power Dissipation Rating Per Section In Watts:
8.0 free air single section

NSN 5905-00-556-6565

Fiig: A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Resistance Tolerance Per Section In Percent:
-2.0 to 2.0 single section
Actuator Travel Control Feature:
Continuous motion
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
2 binding post
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No