## NSN 5905-00-556-6991

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-556-6991 **Section Quantity:** 1 **Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** 0.7500 inches Pilot Length: 0.0620 inches **Undercut Diameter:** 1.820 inches **Undercut Width:** 0.0620 inches **Body Diameter:** 2.000 inches **Angle Of Mounting Hole In Deg:** 90.0 **Angle Between Centerlines Of Mounting Holes In Deg:** 120.0 **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.750 inches **Body Length:** 1.984 inches **Mounting Lip Diameter:** 1.8750 inches **Mounting Lip Depth:** 0.0620 inches **Mounting Hole/stud Circle Diameter:** 1.250 inches **Shaft Style:** Round **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 3600.0 **Maximum Starting Torque:** 

1.30 inch-ounces **Maximum Running Torque:** 

0.90 inch-ounces

## NSN 5905-00-556-6991

Precision Wire Wound Variable Resistor - Page 2 of 3



Shaft End Play:	
0.00100 inches	
Shaft Runout:	
0.0015 inches	
Lateral Runout:	
0.001 inches	
Pilot Diameter Runout:	
0.00100 inches	
Shaft Radial Play:	
0.001 inches	
Screw Thread Diameter:	
0.164 inches	
Screw Thread Series Designator:	
Unc	
Screw Thready Qty Per Inch (tpi):	
32.0	
Mounting Facility Quantity:	
3	
Terminal Location:	
Radially positioned over less than half the circumference	
Mounting Method:	
Threaded hole	
Features Provided:	
Hermetically sealed	
Electrical Resistance Per Section:	
1.800 kilohms single section	
Rotary Actuator Travel In Angular Deg:	
3600.0	
Function Conformity Tolerance Per Section:	
-0.05/+0.05 single section	
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:	
80.0 single section	
Power Dissipation Rating Per Section In Watts:	
5.0 free air single section	
Function Conformity Per Section:	
Single section independent linearity	
Resistance Tolerance Per Section In Percent:	
-1.0/+1.0 single section	
Actuator Travel Control Feature:	
Stops	
Function Characteristic Per Section:	
Single section linear	
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:	

40.0 single section

## NSN 5905-00-556-6991

Precision Wire Wound Variable Resistor - Page 3 of 3



Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0