NSN 5905-00-556-7912

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-556-7912

Section Quantity:
1
Body Style:
Rectangular w/mounting holes/slots
Overall Length:
1.290 inches
Terminal Length:
12.000 inches
Overall Height:
0.325 inches
Overall Width:
0.295 inches
Mounting Hole Diameter:
Between 0.088 inches and 0.094 inches
Shaft Diameter:
0.125 inches
Shaft Length:
Between 0.020 inches and 0.060 inches
Body Length:
Between 1.230 inches and 1.270 inches
Body Width:
Between 0.230 inches and 0.270 inches
Body Height:
0.325 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Lateral Distance Between Mounting Hole Centers:
Between 0.995 inches and 1.005 inches
Mounting Facility Quantity:
2
Terminal Location:
Rear end
Mounting Method:
Unthreaded hole
Electrical Resistance Per Section:
20.000 kilohms single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-800.0 to 800.0 single section
Power Dissipation Rating Per Section In Watts:

0.2 free air single section

NSN 5905-00-556-7912

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Resistance Tolerance Per Section In Percent:

-20.0 to 20.0 single section

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

40.0 single section

Standard Taper Curve Per Section:

A single section

Special Features:

Derated to 0.02 watt at 100 degrees c

Terminal Type And Quantity:

3 wire lead

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

No

Fiig:

A002a0