## NSN 5905-00-557-4598

Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-557-4598

0.60 inch-ounces

## NSN 5905-00-557-4598

Precision Wire Wound Variable Resistor - Page 2 of 2



Lateral Runout:
0.001 inches
Pilot Diameter Runout:
0.00100 inches
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Flange
Electrical Resistance Per Section:
157.0 ohms single section
Tap Location From Ccw Terminal Per Section In Deg Of Effective Electrical Rotation:
2230.0 single section
Rotary Actuator Travel In Angular Deg:
3600.0
Function Conformity Tolerance Per Section:
-0.50/+0.50 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
80.0 single section
Power Dissipation Rating Per Section In Watts:
2.0 free air single section
Function Conformity Per Section:
Single section independent linearity
Fixed Tap Quantity Per Section:
1 single section
Resistance Tolerance Per Section In Percent:
-3.0/+3.0 single section
Actuator Travel Control Feature:
Stops
Function Characteristic Per Section:
Single section linear
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 single section
Terminal Type And Quantity:
4 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A002a0