

View Online at https://aerobasegroup.com/nsn/5905-00-557-4641

## Section Quantity:

1

Body Style:

Cylindrical bushing mounted

## **Reliability Indicator:**

Not established

## **Body Diameter:**

1.062 inches

#### Shaft Diameter:

0.250 inches

Shaft Length:

0.625 inches

#### Mounting Bushing Length:

0.500 inches

## Body Length:

## 0.562 inches

Shaft Style:

Round, slotted

## Actuator Type:

Single shaft

## Effective Electrical Rotation In Deg Angular Rotation:

295.0

## Nonturn Device Location:

At 9 oclock

## Nonturn Device Radius:

0.531 inches

#### Screw Thread Diameter:

0.375 inches

#### Screw Thread Series Designator:

Unef

## Screw Thready Qty Per Inch (tpi):

32.0

## **Terminal Location:**

Radially positioned over less than half the circumference

## Mounting Method:

Standard bushing

## **Electrical Resistance Per Section:**

100.000 kilohms single section

# Rotary Actuator Travel In Angular Deg:

295.0

## Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

120.0 single section

# NSN 5905-00-557-4641 Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Power Dissipation Rating Per Section In Watts:

2.0 free air single section

## **Resistance Tolerance Per Section In Percent:**

-10.0 to 10.0 single section

## Actuator Travel Control Feature:

Stops

## Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

C single section

## Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

#### Unit Of Measure:

--

## Demilitarization:

No

## Fiig:

A002a0