NSN 5905-00-557-5561

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-557-5561 **Section Quantity:** 2 **Body Style:** Cylindrical hole/slot mounted **Reliability Indicator:** Not established **Body Diameter:** 1.250 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 1.000 inches **Body Length:** 2.312 inches **Mounting Hole/stud Circle Diameter:** 0.750 inches **Shaft Style:** Round **Actuator Type:** Single shaft **Screw Thread Diameter:** 0.112 inches **Screw Thread Series Designator:** Unc Screw Thready Qty Per Inch (tpi): 40.0 **Mounting Facility Quantity: Terminal Location:** Radially positioned over less than half the circumference **Mounting Method:** Threaded hole **Features Provided:** Nonmetallic shaft **Electrical Resistance Per Section:** 50.000 kilohms all sections Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 105.0 all sections **Power Dissipation Rating Per Section In Watts:** 2.0 free air all sections

Resistance Tolerance Per Section In Percent:

-5.0 to 5.0 all sections

NSN 5905-00-557-5561

Fiig: A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:	
40.0 all sections	
Standard Taper Curve Per Section:	
A all sections	
Terminal Type And Quantity:	
6 solder stud	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	