NSN 5905-00-557-7953

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-557-7953 **Section Quantity: Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** 1.957 inches **Body Diameter:** 1.680 inches **Shaft Diameter:** Between 0.248 inches and 0.251 inches **Shaft Length:** Between 0.453 inches and 0.547 inches **Mounting Bushing Length:** Between 0.328 inches and 0.422 inches **Body Length:** 1.410 inches **Overall Diameter:** 2.260 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Maximum Starting Torque:** 40.00 inch-ounces **Maximum Stop Torque:** 240.00 inch-ounces **Nonturn Device Location:** At 12 oclock **Nonturn Device Radius:** Between 0.485 inches and 0.515 inches **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Mounting Facility Quantity:**

Terminal Location:

Radially positioned over less than half the circumference

NSN 5905-00-557-7953

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Mounting Method: Standard bushing Electrical Resistance Per Section: 35.000 ohms single section	
Electrical Resistance Per Section:	
35.000 ohms single section	
Rotary Actuator Travel In Angular Deg:	
Between 275.0 and 305.0	
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:	
340.0 single section	
Power Dissipation Rating Per Section In Watts:	
25.0 heat sink single section	
Resistance Tolerance Per Section In Percent:	
-10.0 to 10.0 single section	
Actuator Travel Control Feature:	
Stops	
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:	
25.0 single section	
Standard Taper Curve Per Section:	
A single section	
Test Data Document:	
81349-mil-r-22 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification form	at
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmenta	I
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).	
Terminal Type And Quantity:	
3 tab, solder lug	
Specification Data:	
81349-mil-r-22/3 government specification	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A002a0	