NSN 5905-00-557-9094

Section Quantity:

Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-557-9094

Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Body Diameter:
Between 1.656 inches and 1.719 inches
Shaft Diameter:
Between 0.248 inches and 0.250 inches
Shaft Length:
2.000 inches
Mounting Bushing Length:
0.375 inches
Body Length:
Between 0.750 inches and 0.812 inches
Shaft Style:
Round
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
280.0
Maximum Starting Torque:
maximum starting rollque.
6.00 inch-ounces
6.00 inch-ounces
6.00 inch-ounces Maximum Running Torque:
6.00 inch-ounces Maximum Running Torque: 6.00 inch-ounces
6.00 inch-ounces Maximum Running Torque: 6.00 inch-ounces Maximum Stop Torque:
6.00 inch-ounces Maximum Running Torque: 6.00 inch-ounces Maximum Stop Torque: 128.00 inch-ounces
6.00 inch-ounces Maximum Running Torque: 6.00 inch-ounces Maximum Stop Torque: 128.00 inch-ounces Nonturn Device Location:
6.00 inch-ounces Maximum Running Torque: 6.00 inch-ounces Maximum Stop Torque: 128.00 inch-ounces Nonturn Device Location: At 9 oclock
6.00 inch-ounces Maximum Running Torque: 6.00 inch-ounces Maximum Stop Torque: 128.00 inch-ounces Nonturn Device Location: At 9 oclock Nonturn Device Radius:
6.00 inch-ounces Maximum Running Torque: 6.00 inch-ounces Maximum Stop Torque: 128.00 inch-ounces Nonturn Device Location: At 9 oclock Nonturn Device Radius: Between 0.516 inches and 0.547 inches
6.00 inch-ounces Maximum Running Torque: 6.00 inch-ounces Maximum Stop Torque: 128.00 inch-ounces Nonturn Device Location: At 9 oclock Nonturn Device Radius: Between 0.516 inches and 0.547 inches Screw Thread Diameter:
6.00 inch-ounces Maximum Running Torque: 6.00 inch-ounces Maximum Stop Torque: 128.00 inch-ounces Nonturn Device Location: At 9 oclock Nonturn Device Radius: Between 0.516 inches and 0.547 inches Screw Thread Diameter: 0.375 inches
6.00 inch-ounces Maximum Running Torque: 6.00 inch-ounces Maximum Stop Torque: 128.00 inch-ounces Nonturn Device Location: At 9 oclock Nonturn Device Radius: Between 0.516 inches and 0.547 inches Screw Thread Diameter: 0.375 inches Screw Thread Series Designator:
6.00 inch-ounces Maximum Running Torque: 6.00 inch-ounces Maximum Stop Torque: 128.00 inch-ounces Nonturn Device Location: At 9 oclock Nonturn Device Radius: Between 0.516 inches and 0.547 inches Screw Thread Diameter: 0.375 inches Screw Thread Series Designator: Unef
6.00 inch-ounces Maximum Running Torque: 6.00 inch-ounces Maximum Stop Torque: 128.00 inch-ounces Nonturn Device Location: At 9 oclock Nonturn Device Radius: Between 0.516 inches and 0.547 inches Screw Thread Diameter: 0.375 inches Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi):
Maximum Running Torque: 6.00 inch-ounces Maximum Stop Torque: 128.00 inch-ounces Nonturn Device Location: At 9 oclock Nonturn Device Radius: Between 0.516 inches and 0.547 inches Screw Thread Diameter: 0.375 inches Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): 32.0
Maximum Running Torque: 6.00 inch-ounces Maximum Stop Torque: 128.00 inch-ounces Nonturn Device Location: At 9 oclock Nonturn Device Radius: Between 0.516 inches and 0.547 inches Screw Thread Diameter: 0.375 inches Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): 32.0 Terminal Location:
Maximum Running Torque: 6.00 inch-ounces Maximum Stop Torque: 128.00 inch-ounces Nonturn Device Location: At 9 oclock Nonturn Device Radius: Between 0.516 inches and 0.547 inches Screw Thread Diameter: 0.375 inches Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): 32.0 Terminal Location: Radially positioned over less than half the circumference

NSN 5905-00-557-9094

Precision Wire Wound Variable Resistor - Page 2 of 2



Features Provided:
Humidity proof
Electrical Resistance Per Section:
50.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
300.0
Function Conformity Tolerance Per Section:
-1.00/+1.00 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
105.0 single section
Power Dissipation Rating Per Section In Watts:
4.0 free air single section
Function Conformity Per Section:
Single section independent linearity
Resistance Tolerance Per Section In Percent:
-5.0/+5.0 single section
Actuator Travel Control Feature:
Stops
Function Characteristic Per Section:
Single section linear
Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:
-0.0/+130.0 single section
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 single section
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:
A002a0